



## SVS-603HR and SVS-603HRB Wave Sensors

The SVS-603HR and SVS-603HRB\* wave sensors are an augmented version of the highly accurate SVS-603 wave sensor that reports heading, wave height, wave period and wave direction via RS-232 or logs to its on-board data logger. The SVS-603HR and SVS-603HRB represent a new generation in accuracy and completeness for wave sensing electronics whose features include:

- Very low power consumption; fits the smallest power budget
- Very small footprint; sold packaged or as bare PCB
- Sensors account for 3-D motion, rotation and compass heading in all dimensions to cover nine degrees of freedom
- Sophisticated onboard electronics provide near-real-time wave statistics
- Variable sample set size (256, 512, 1024, 2048 or 4096)
- On-board temperature compensation
- On-board data logger capable of logging as much as twenty years of wave data, depending on desired outputs.
- Easy configuration to match your exact sensing rate and output requirements
- Readily interfaced with transmitter using NMEA or other configurable data output
- Sampling rates from 1 to 8Hz (user configurable)
- Horizontal and vertical offset correction algorithms to allow free positioning of sensor
- Orientation controls to allow for placing the sensor in any orientation

\*The SVS-603HR and SVS-603HRB have very similar form factors. They have the exact same horizontal dimensions and mounting hole pattern. The SVS-603HRB is less than 4 mm taller. Some of the components are re-arranged. For example, the watch battery is on the bottom of the SVS-603HRB board (which accounts for the change in height) and the SD card slot is on the side of the SVS-603HRB board which requires some horizontal clearance for retrieving the card.



The SVS-603HR and SVS-603HRB can be used to replace existing sensors, to upgrade existing buoys, or to add wave sensing capabilities to even the most compact buoys. Among the wave data that are available as outputs from the sensor are:

- Significant wave height ( $H_s$ ) including wind and swell components
- Wave period (several formulations)
- Wave direction in degrees from north
- North, east and up displacement time series
- First-5 Fourier wave coefficients
- Maximum wave height ( $H_{max}$ )
- Wave period at  $H_{max}$
- Wave energy
- Spectrum (raw or processed)
- Heading in degrees
- Comprehensive set of output parameters

Other outputs or data manipulations can be incorporated via firmware updates or through calculations on the available data stream.



<b>Output Formats:</b>	Hex code defined output parameters
	NMEA
	First-5 Fourier coefficients
	Wave energy spectrum
<b>Accuracy Metrics:</b>	
Hs: 1cm @ 0.1m, 2cm @ 1.5m, 10cm @ 25m	0.1m to 25m Resolution 0.001 m
Period: 0.02sec @ 1sec, 0.04sec @ 2sec, 0.1sec @ 20sec	1.0 – 30 sec, Resolution 0.001 sec
Wave Direction $\pm 1^\circ$ *	Range 0-360°; Resolution 0.001°
Heave 0.1m	Range $\pm 25$ m, Resolution 0.01m
<b>Available Ports and Slots:</b>	RS232 Adjustable baud rate (2400 - 230400)
	USB Micro-B
	Micro-SD
<b>Dimensions:</b>	53.5mm length
	68mm width
	23mm height (HR)/26.7mm (HRB) (w/connector)
<b>Weight:</b>	Bare board: 1.4oz/40g
	In enclosure: 15oz/425g
<b>Power Requirements:</b>	151mW@12V
	138mW@5V
	5-30VDC
<b>Temperature:</b>	Operating: -40C to 85C ** Storage: -40C to 85C

\* Dependent on orbital buoy motion    \*\* Industrial SD card required

